




| SI. NO. | ITEM DESCRIPTION | IMAGE | IMAGE |
|---------|---|---|---|
| 1 | Square Open Cell Ceiling :Supply of LDSquare Make 100mmx100mm Open Cell Ceiling system of 0.4mmGI thickness & 40mm ht, U bend with U size 9mmx 40 x40 in powder coated finish of approved shade(The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 545x545mm with end clips /mounting clips . The tile would be hung through GI WIRE , M6 Hook type anchor fastner , butterfly clip . The ceiling and the accessories would be provided with powder coated finish of thickness 70-80 microns. Powder Coating Color:- Any RAL Color Of Your Choice. |  |  |
| 2 | Square Open Cell Grid Ceiling :Supply of LDSquare Make 90mmx90mm Open Cell Ceiling system of 0.4mmGI thickness & 40mm ht, U bend with U size 9mmx 40 x40 in powder coated finish of approved shade(The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 600x600mm whcih would be placed inside the 15mm T grid of powder coated finish . The tile would be hung through GI WIRE , M6 Hook type anchor fastner , butterfly clip . The ceiling and the accessories would be provided with powder coated finish of thickness 70-80 microns. Powder Coating Color:- Any RAL Color Of Your Choice. | | |
| 3 | Square Open Cell Ceiling :Supply of LDSquare Make 50mmx50mm Open Cell Ceiling system of 0.4mm GI thickness & 40mm ht, U bend with U size 9mmx 40 x40 in powder coated finish of approved shade(The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 590x590mm with end clips /mounting clips . The tile would be hung through GI WIRE , M6 Hook type anchor fastner , butterfly clip . The ceiling and the accessories would be provided with powder coated finish of thickness 70-80 microns. Powder Coating Color:- Any Color Of Your Choice. | | |
| 4 | Square Open Cell Ceiling :Supply of LDSquare Make 300mmx300mm Open Cell Ceiling system of 0.4mm GI thickness & 40mm ht, U bend with U size 9mmx 40 x40 in powder coated finish of approved shade(The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 1030x1030mm with end clips /mounting clips . The tile would be hung through GI WIRE , M6 Hook type anchor fastner , butterfly clip . The ceiling and the accessories would be provided with powder coated finish of thickness 70-80 microns. Powder Coating Color:- Any Color Of Your Choice. | | |
| 5 | Same as the above For 75x75mm open cell , the size of the total cell would be 580x580mm | | |
| 6 | Same as the above For 100x100mm open cell , the size of the total cell would be 545x545mm | | |
| 7 | Same as the above For 125x125mm open cell , the size of the total cell would be 530x530mm | | |
| 8 | Same as the above For 150x150mm open cell , the size of the total cell would be 477X477mm | | |
| 9 | Same as the above For 200x200mm open cell , the size of the total cell would be 627X627mm | | |

| | | | |
|----|--|---|--|
| 10 | <p>Triangle Open Cell:Supply of LDSquare Triangle Open Cell Ceiling 100mm equilateral triangle Open Cell Ceiling system of 0.4mm GI thickness & 40mm ht, U bend with U size 9mmx 40 x40 in powder coated finish of approved shade.The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 1016x1016mm with end clips /mounting clips . The tile would be hung to the true ceiling by using M6 hook type anchor fastner , nut and washer with Gi wire and butterfly clip , the ceiling and the accessories would be provided with powder coated finish of 70-80 microns thickness.Powder Coating Color:Any RAL color Of Your Choice.</p> |  |  |
| 11 | <p>Triangle Open Cell: Supply of LDSquare Triangle Open Cell Ceiling of 300mm equilateral triangle Open Cell Ceiling system of 0.4mm GI thickness & 40mm ht, U bend with U size 25mmx 40 x40 in powder coated finish of approved shade.The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 1016x1016mm with end clips /mounting clips . The tile would be hung to the true ceiling by using M6 hook type anchor fastner , nut and washer with Gi wire and butterfly clip , the ceiling and the accessories would be provided with powder coated finish of 70-80 microns thickness.Powder Coating Color:Any RAL color Of Your Choice.</p> |  |  |
| 12 | <p>Triangle Open Cell: Supply of LDSquare Triangle Open Cell Ceiling 450mm equilateral triangle Open Cell Ceiling system of .1.2mm thickness aluminium & 100mm ht, U bend with U size 50mmx 100x100 in powder coated finish of approved shade.The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 1016x1016mm with end clips /mounting clips . The tile would be hung to the true ceiling by using M6 hook type anchor fastner , nut and washer with Gi wire and butterfly clip , the ceiling and the accessories would be provided with powder coated finish of 70-80 microns thickness.Powder Coating Color:Any color Of Your Choice.</p> |  |  |
| 13 | <p>Triangle Open Cell: Supply of LDSquare Triangle Open Cell Ceiling 550 X 550mm 90 degree triangle Open Cell Ceiling system of 0.6mm GI thickness & 150mm ht, U bend with U size 25 x150mm in powder coated finish of approved shade.The long channel and short channel would be at the same level interlocked in each cell .The tile would be hung to the true ceiling by using M6 hook type anchor fastner , nut and washer with Gi wire and butterfly clip , the ceiling and the accessories would be provided with powder coated finish of 70-80 microns thickness.Powder Coating Color: Wooden Grain Finish.</p> |  |  |
| 14 | <p>Triangle Open Cell Grid Ceiling :Supply of LDSquare Make 189X189mm Open Cell Ceiling system of 0.4mmGI thickness & 40mm ht, U bend with U size 9mmx 40 x40 in powder coated finish of approved shade , inside which 125mm triangles are formed(The long channel and short channel would be at the same level interlocked in each cell . The size of the total cell would be 600x600mm whcih would be placed inside the 15mm T grid of powder coated finish . The tile would be hung through GI WIRE , M6 Hook type anchor fastner , butterfly clip . The ceiling and the accessories would be provided with powder coated finish of thickness 70-80 microns. Powder Coating Color:- Any Color Of Your Choice.</p> |  | |

| | | | |
|----|--|---|--|
| 15 | <p>Cafeteria Tile:- Supply of LDSquare Make Providing and fixing in true level, Open cell ‘Lock-in’ ceiling containing ‘U’ shaped sections with sharp edges of dimensions 8mm (Flange width) X 40mm (web height) manufactured out of GI of 0.40 mm gauge of White color as approved. The open cell ‘Lock-in’ ceilings shall have 3 components viz. Open cell panels (top and bottom notches) of length 600mm and 1200mm, cross rails of length 1200mm, mounting rails of length 2000mm long. The Open Cell panels shall have notches on top or bottom spaced at 100mm to be used with matching mounting rails and cross rails. Model Number - 22-02-1</p> |  | |
|----|--|---|--|