



















Sl. NO.	ITEM DESCRIPTION	IMAGE	IMAGE
5	Baffle Grid Ceiling : Supply of LD Square Make baffle ceiling this shall consist of 'Box' shaped 0.8mm thick aluminium extruded section , The size of the 'Box' sections shall be 50x50mm to form cell size 600mm (which can be modified as per architect/designers requirement). available in length of 3200mm .which can be modified as per the architect design .The baffles shall be fixed to each other using framework of size 25mmx15mm made using 0.8mm thick GI sheet which is folded and bent to desired profile finished with powder coating. These mild steel framework/sections shall be inserted between two members and fixed using self interlocking system. The mild steel framework in turn are fixed on to the true ceiling above using a suitable suspension system consisting of nuts, Washers, 6mm GI rod and anchor fasteners. This ceiling facilitates easy maintenance. Rate to includes necessary supports as per manufacturer specification. The ceiling and the accessories are provided with powder coated thickness of 70-80 microns.powder coating color: Any color of your choice.		
6	Baffle Grid Ceiling : Supply of LD Square Make baffle ceiling this shall consist of 'U' shaped 0.5mm thick GAL sheet section , The size of the 'U' sections shall be 50x50mm to form cell size 600mm (which can be modified as per architect/designers requirement). available in length of 3200mm .which can be modified as per the architect design .The baffles shall be fixed to each other using framework of size 25mmx15mm made using 0.8mm thick GI sheet which is folded and bent to desired profile finished with powder coating. These mild steel framework/sections shall be inserted between two members and fixed using self interlocking system. The mild steel framework in turn are fixed on to the true ceiling above using a suitable suspension system consisting of nuts, Washers, 6mm GI rod and anchor fasteners. This ceiling facilitates easy maintenance. Rate to includes necessary supports as per manufacturer specification. The ceiling and the accessories are provided with powder coated thickness of 70-80 microns.powder coating color: Any color of your choice.		
8	Baffle Grid with Perforated Ceiling : Supply of LD Square Make baffle ceiling this shall consist of 'U' shaped 0.5mm thick GAL sheet section , The size of the 'U' sections shall be 25x50mm to form cell size 900mm (which can be modified as per architect/designers requirement). available in length of 3200mm the grid would be provided with 900x900mm perforated tile of 0.6mm thick with perforation diameter 15mm with triangular pitch.which can be modified as per the architect design .The baffles shall be fixed to each other using framework of size 25mmx15mm made using 0.8mm thick GI sheet which is folded and bent to desired profile finished with powder coating. These mild steel framework/sections shall be inserted between two members and fixed using self interlocking system. The mild steel framework in turn are fixed on to the true ceiling above using a suitable suspension system consisting of nuts, Washers, 6mm GI rod and anchor fasteners. This ceiling facilitates easy maintenance. Rate to includes necessary supports as per manufacturer specification. The ceiling and the accessories are provided with powder coated thickness of 70-80 microns.powder coating color: Any color of your choice.		
9	Baffle Grid with Mesh Ceiling: Supply Of LD Square Make Expandable 3D Mesh Ceiling Made of 1.2mm CRCA sheet to form a hex formation of 38mm/16mm diamond structure the tile to powder coated in any regular matt finish as approved by the architect /client the size of the tile would be 600mmx600mm to be placed inside the 50x50mm box section made up of 0.5mm thick gal sheet and is to supported by M6 anchor fastner , threaded rod , washer and nut @ every 800 mm and the cut tiles for the services need to factory finished the tile. Make LDsquare . Part Number - 500003		
11	Metal String Ceiling : Supply & Installation of Id square make metal string ceiling made up of 10mm diameter hollow pipe of thickness 1.6mm , the pipe material would be MS and the pipe would be provided with powder coated finish of thickness 70-80 microns , the color would be multicolors as per the architect approval , the pipe would be fixed inserted inside the hole which is provided on the baffle wall and lock pin would be provided to fix the pipe inside the baffle to arrest the degree of freedom(it does not come out) , the pipe would be of 600mm length and place at distance of 60mm each other . The pipe would be fixed at the centre of the baffle height .The baffle grid would be formed at cell size 600mm and baffle size would be 30x100mm which is made up of 0.5 thick galvalum sheet section and baffle grid would be provided with wooden grain finish of approved color , The ceiling would be hung to the true ceiling by using hilti make M6 anchor fastner , M6 GI threaded rod , washer and nut and the support would be provided at every 800mm.		
1	Hexagonal Open Cell Ceiling: Supply of LD Square Metal Make Ceiling of 150mm hexagonal Open Cell Ceiling system of 0.9mm thickness & 100mm ht, U bend with U size 25mmx 100 x100 in powder coated finish of approved shade(The long channel and short channel would be 659X659MM at the same level interlocked in each cell . The size of the total cell would be 6mm with end clips /mounting clips . The tile would be hung through clip channel and threaded rods through anchor fastners.with powder coating finish Of Color Any color.		
2	Perforated Hexagonal Ceiling : Supply of LD Square Hexagonal ceiling made up of 0.8 mm GI sheet with perforation of 8 X 32 mm of size 300mm , the tile would be hung to the true ceiling by clip in system , the clip channel would be made up of 0.4mm GI which would be hung to the true ceiling by using M6 anchor fastner M6, washer and nut . The tile would be given with powder coated finish of thickness 70 microns , Powder coating color : Any color of your choice.		
3	Hexagonal Mesh Ceiling		
4	Hexagonal Baffle Ceiling		

SI. NO.	ITEM DESCRIPTION	IMAGE	IMAGE
1	<p>Hexagonal Open Cell Ceiling: Supply of LD Square Metal Make Ceiling of 150mm hexagonal Open Cell Ceiling system of 0.9mm thickness & 100mm ht, U bend with U size 25mmx 100 x100 in powder coated finish of approved shade(The long channel and short channel would be 659X659MM at the same level interlocked in each cell . The size of the total cell would be 6mm with end clips /mounting clips . The tile would be hung through clip channel and threaded rods through anchor fastners.with powder coating finish Of Color Any color.</p>		
2	<p>Perforated Hexagonal Ceiling : Supply of LD Square Hexagonal ceiling made up of 0.8 mm GI sheet with perforation of 8 X 32 mm of size 300mm, the tile would be hung to the true ceiling by clip in system , the clip channel would be made up of 0.4mm GI which would be hung to the true ceiling by using M6 anchor fastner M6, washer and nut . The tile would be given with powder coated finish of thickness 70 microns , Powder coating color :Any color of your choice.</p>		
3	<p>Hexagonal Mesh Ceiling</p>		
4	<p>Hexagonal Baffle Ceiling</p>	